



FAST[®] BUMP

High Cut Helmet System



The FAST Bump high cut shell is designed for less extreme environments where ballistic threats are not a priority, and the focus is on protection from blunt trauma forces, or where the primary need is for integration of mission-configured components.

- Rigid polymer High-cut shell with eight vent holes to provide increased airflow and reduce heat stress
- Vented Lux Liner with Low Profile Occ-Dial and Head-Loc Retention System offering enhanced impact protection and unmatched stability and comfort
- Modular Bungee Shroud (MBS) for compatibility with most NVG mounts and integrated NVG retention system
- Features PowerPath ARC rails with improved cable management and accessory integration.

SPECIFICATIONS

Performance Specification: BS EN 1385: 2012, ACH CO/PD 05-04: 2007, PS-1145

Shell Construction: Injection Molded Glass Filled Nylon

Areal Density: N/A

Shell Thickness: 0.138" (3.50 mm)

Shell Geometry (Curvature): FAST Curvature

Cut Style (Side Protection): High Cut

Available Colors:

- Urban Tan
- Ranger Green
- Black
- MultiCam[®]

Available Sizes: Medium, Large, X-Large, XX-Large

Available Sizes	Medium	Large	X-Large	XX-Large
Head Size (Circumference)	20 7/8 - 22 in (53-56 cm)	22 - 23 1/4 in (56-59 cm)	23 1/4 - 24 3/8 in (59-62 cm)	24 3/8 - 25 1/2 in (62-64 cm)
Square Coverage	132 in ² (852 cm ²)	143 in ² (923 cm ²)	157 in ² (1013 cm ²)	165 in ² (1065 cm ²)
Shell Weight	1.75 lbs (796 g)	1.84 lbs (835 g)	1.96 lbs (890g)	2.10 lbs (957g)

Note: All measurements are +/- 3% tolerance

Contact Us

Ops-Core is committed to designing advanced performance capabilities for the elite warrior. For more information regarding the Ops-Core FAST Bump High Cut Helmet System, contact Ops-Core at 617.670.3547 or sales@ops-core.com. The FAST Bump is subject to the U.S. Export Administration Regulations (EAR) 15 CFR 730-774. The export of this item and related technical information may require prior authorization from the U.S. Government.